

FIBER OPTIC TERMINAL BOX MODEL 1STB

Our is compact and flexible in whole parts, simple in structure, easy in operation.
The box combines fiber tray with flap, it will be more practical.
Max capacity cores of 8 SC Simplex.



Dimensions (mm)	208.5*204*54
Material	ABS
Weight (kg)	0.8 ~ 1.0
Operating Temperature (°C)	-25°C ~ +45°C
Protection grade	IP55
Packing	1 box of 46*44*33cm : 20 units

ORDERING INFORMATION											
Type	Adapter	Polishing		Type	Colors		Ports	Fiber		Length (m)	
1STB	FC	A	APC	D	Duplex	1	Aqua	1	OS1	G.652B	1
	E2000	U	UPC	Q	Quad	2	Blue	2	OS2	G.652D	2
	LC			S	Simplex	3	Beige	3	655	G.655	3
	MU					4	Green	4	657	G.657	
	SC					5	12 colors	OM1	62.5/125	
	ST					6	Yellow	14	OM2	50/125	
								15	OM3	50/125	
								16	OM4	50/125	

ORDERING INFORMATION EXAMPLE

1STB	LC	U	D	6	6	OS2	1
------	----	---	---	---	---	-----	---

Configuration: Outdoor terminal box Model 1STB LC UPC DX 12 Yellow OS2 1mt pigtails

HONG KONG

Romatecsans International Limited
7/F., Catic Building, No. 44 Tsun Yip
Street, Kowloon, Hong Kong
Tel. +852 8199 9706
asia@romatecsans.com

CHILE

Importadora y Exportadora Romatecsans Ltda.
Carmen Farina 6758, Vitacura,
Santiago, Chile
Tel.: +56 22 9797 922
ventas@romatecsans.com

sales@romatecsans.com
www.romatecsans.com

