

TECHNICAL SPECIFICATION

COPPER CAT. 6A PATCH CORD

We have a complete structured cabling solution, where our products are manufactured under the UL and ETL standards. We provide to our customers 25 years guarantee on our structured cabling solution.



Standards	ISO/IEC 11801 TIA/EIA568B.2
Multi construction	4 Pairs (8 cores)
AWG	24
Conductor Material	Bare Copper
Diameter of the Dielectric Core (mm)	7*0.16
Outer Diameter (mm)	6.2 ± 0.2
Jacket	PVC / LSZH
Operating Temperature (°C)	-25 ~ +65
Operating Life	750 insertion cycles
Contact Material	Phosphor Bronze
Contact Plating	60 micro-inch Gold
Housing Material	PC UL94V-0
Rated Voltage (V)	150V
Current Rating	1.5A
Contact Resistance	Max. 20mΩ
Insulation Resistance	500mΩ
Dielectric Withstanding Voltage	1000V RMS

HONG KONG

Romatecsans International Limited
7/F., Catic Building, No. 44 Tsun Yip
Street, Kowloon, Hong Kong
Tel. +852 8199 9706
asia@romatecsans.com

CHILE

Importadora y Exportadora Romatecsans Ltda.
Carmen Farina 6758, Vitacura,
Santiago, Chile
Tel.: +56 22 9797 922
ventas@romatecsans.com

sales@romatecsans.com
www.romatecsans.com



TECHNICAL SPECIFICATION

ORDERING INFORMATION								
Model	Category	Type		Color		Jacket		Length (m)
PC	5e	1	<i>UUTP</i>	1	<i>Yellow</i>	A	<i>LSZH</i>	1
	6	2	<i>FUTP</i>	2	<i>Blue</i>	B	<i>PVC</i>	2
	6a	3	<i>UFTP</i>	3	<i>White</i>			3
		4	<i>FFTP</i>	4	<i>Metal</i>			4
		5	<i>SUTP</i>	5	<i>Red</i>		
		6	<i>SFTP</i>	6	<i>Green</i>			120
ORDERING INFORMATION EXAMPLE								
PC	6a	6		3		A		30

Configuration: Patch Cord Cat. 6a SFTP White LSZH 30mts

HONG KONG

Romatecsans International Limited
7/F., Catic Building, No. 44 Tsun Yip
Street, Kowloon, Hong Kong
Tel. +852 8199 9706
asia@romatecsans.com

CHILE

Importadora y Exportadora Romatecsans Ltda.
Carmen Farina 6758, Vitacura,
Santiago, Chile
Tel.: +56 22 9797 922
ventas@romatecsans.com

sales@romatecsans.com
www.romatecsans.com

