

COPPER CAT. 6 PATCH CORD

We have a complete structured cabling solution, where our products are manufactured under the UL and ETL standards. We provide to our customers 25 years guarantee on our structured cabling solution.



Standards	ISO/IEC 11801
	TIA/EIA568B.2
Multi construction	4 Pairs (8 cores)
AWG	24
Conductor Material	Bare Copper
Diameter of the Dielectric Core (mm)	7*0.2
Outer Diameter (mm)	5.8 ± 0.2
Jacket	PVC / LSZH
Operating Temperature (°C)	-25 ~ +65
Operating Life	750 insertion cycles
Contact Material	Phosphor Bronze
Contact Plating	60 micro-inch Gold
Housing Material	PC UL94V-0
Rated Voltage (V)	150V
Current Rating	1.5A
Contact Resistance	Max. 20mΩ
Insulation Resistance	500mΩ
Dielectric Withstanding Voltage	1000V RMS

HONG KONG

Romatecsans International Limited
7/F., Catic Building, No. 44 Tsun Yip
Street, Kowloon, Hong Kong
Tel. +852 8199 9706
asia@romatecsans.com

CHILE

Importadora y Exportadora Romatecsans Ltda.
Carmen Farina 6758, Vitacura,
Santiago, Chile
Tel.: +56 22 9797 922
ventas@romatecsans.com

sales@romatecsans.com
www.romatecsans.com

