


FIBER OPTIC ADAPTERS

Romatecsans offers an extensive range of adapters, based on our customer need. The maximum insertion loss does not exceed $\leq 0.2\text{dB}$ and are manufactured under the telecommunications quality standards.



	FC, E2000, MU, LC.LX.5, SC & ST Adapters	
Mode	SM (UPC & APC)	MM
Insertion Loss	$\leq 0.2\text{dB}$	$\leq 0.3\text{dB}$
Return Loss	$\geq 45\text{dB}$	N/A
Mating Durability (500 times)	Additional Loss $\leq 0.1\text{dB}$, Return Loss Variability $< 5\text{dB}$	
Temperature Stability (-40°C~85°C)	Additional Loss $\leq 0.1\text{dB}$, Return Loss Variability $< 5\text{dB}$	
Operating Temperature	-40°C~+85°C	
Storage Temperature	-40°C~+85°C	

ORDERING INFORMATION

Connector	Fibre		Type		Ports		Material		Color		Product	
FC	SM	Singlemode	A	APC	SX	Simplex	M	Metal	1	Aqua	A	Adapter
E2000	MM	Multimode	U	UPC	DX	Duplex	P	Plastic	2	Blue		
LC					QD	Quad			3	Beige		
LX.5									4	Green		
SC									5	Red		
ST									6	Yellow		

ORDERING INFORMATION EXAMPLE

LC	SM	A	DX	P	4	A
----	----	---	----	---	---	---

Configuration: LC SM APC Duplex Plastic Green Adapter (LCSMADXP4A)

HONG KONG

Romatecsans International Limited
7/F., Catic Building, No. 44 Tsun Yip
Street, Kowloon, Hong Kong
Tel. +852 8199 9706
asia@romatecsans.com

CHILE

Importadora y Exportadora Romatecsans Ltda.
Carmen Farina 6758, Vitacura,
Santiago, Chile
Tel.: +56 22 9797 922
ventas@romatecsans.com

sales@romatecsans.com
www.romatecsans.com

