


FIBER OPTIC ARMORED BUFFER CABLE

Romatecsans f ber optic armored buffered outdoor cables are ideal for outdoor communications.

Our cables are strong, robust and easy for installations in or out of houses or buildings.



- Outer jacket
- 2. Tight Buffered
- 3. Ripcord
- 4. Inner jacket
- Strength member
- Corrugated steel

Items		Specif cations
Fibers		12
Tight-buffered f ber	Dimensions	850um ± 50um
	Material	PVC
Strength Member		Aramid Yarn
Inner Jacket	Dimensions	6.5mm ± 0.3mm
	Material	LSZH
	Color	Black
Outer Jacket	Dimensions	11.5mm ± 0.5mm
	Material	LSZH
	Color	Black

Mechanical and Environmental Characteristics		
Items	Specif cations	
Tension in Long term (N)	500	
Tension in Short term (N)	1000	
Crush in Long term (N/10cm)	300	
Crush in Short term (N/10cm)	1000	
Min. Bend Radius Dynamic (mm)	20D	
Min. Bend Radius Static (mm)	10D	
Installation Temperature (C)	-20 ~ +60	
Operating Temperature (C)	-40 ~ +70	

Importadora y Exportadora Romatecsans Ltda.

HONG KONG

asia@romatecsans.com

Romatecsans Interna2onal Limited 7/F., Ca) c Building, No. 44 Tsun Yip Street, Kowloon, Hong Kong Tel. +852 8199 9706

CHILE

Tel.: +56 22 9797 922 ventas@romatecsans.com

San) ago, Chile

Carmen Farina 6758, Vitacura,

sales@romatecsans.com www.romatecsans.com

