

TECHNICAL SPECIFICATION

FIBER OPTIC VFL

Designed for field personnel who need an efficient and economical tool for fiber tracing, fiber routing and continuity checking in an optical network during and after installation.



Central Wavelength (nm)	650 ± 10
Emitter Type	FP-LD
Output Power	Optical Choice for 1mw, 5mw, 10mw, 20mw, 30mw, 40mw
Type of connector	2.5mm universal connector For 1.25mm connectors, FC (Male)-LC (Female) convertor can be optional on customer requests
Operating Model	Both CW and Pulse available
Pulse Frequency	2 ~ 3Hz
Power Supply	2*AA Batteries
Operating Temperature (°C)	-20 ~ +60
Storage Temperature (°C)	-40 ~ +85

ORDERING INFORMATION

RSVFL	Power	Range
	1mw	2 ~ 3 km
	5mw	5 km
	10mw	10 km
	20mw	15 ~ 20 km
	30mw	20 ~ 30 km
	40mw	30 ~ 40 km

HONG KONG

Romatecsans International Limited
7/F., Catic Building, No. 44 Tsun Yip
Street, Kowloon, Hong Kong
Tel. +852 8199 9706
asia@romatecsans.com

CHILE

Importadora y Exportadora Romatecsans Ltda.
Carmen Farina 6758, Vitacura,
Santiago, Chile
Tel.: +56 22 9797 922
ventas@romatecsans.com

sales@romatecsans.com
www.romatecsans.com

